

HOW TO TAKE PROPER CARE OF YOUR NEW POOL

1. **NO BRUSHING** POOL FOR THE FIRST FOUR (4) DAYS
2. **NO WALKING IN POOL** AFTER WORKERS HAS FINISHED THE POOL
3. **NO CHEMICALS** FOR THE FIRST THREE (3) DAYS
4. **NO SELF CLEANING MACHINES SUCH AS CRAWLER OR BARRACUDAS** FOR AT LEAST SIX (6) WEEKS
5. **DO NOT STOP THE FLOW OF WATER** ONCE YOU START LOADING THE POOL UNTIL IT REACHES THE CENTER OF THE TILE OR WATERLINE OF TILE. FAILURE TO DO SO WILL RESULT IN A RING IN AROUND THE INSIDE OF THE POOL
6. **PRESERVE ACID LEVEL HIGH** FOR THE FIRST TWO (2) MONTHS. THE POOL WILL CALCIFY IF THE ACID LEVEL IS NOT KEPT HIGH ENOUGH. CALCIFYING OCCURS FROM THE CHEMICALS CLASHING INSTEAD OF DILUTING.
7. **SIGNS OF CALCIFYING**
WHITE ROUGH RESIDUE DEVELOPS ON TILES, LIGHTS AND POOL SURFACE. CAN ALSO CAUSE BAD SPOTS IN THE POOL, CRACKING AND DISCOLORATION OF THE FINISH.